



# Octal FXS/FXO

---

## ATLAS 550 Expansion Modules

### Product Features

#### **OCTAL FXS Module**

- Provides eight FXS local loop interfaces
- All eight interfaces may be mapped to any DS0 on any of the network interfaces or dynamically switched
- Loop start, ground start, PLAR, DPO, and wink delay (for DNIS) operation
- 2-wire interface through an RJ-48 modular connector

#### **OCTAL FXO Module**

- Provides eight foreign exchange office FXO local loop interfaces
- All eight interfaces may be mapped to any DS0 on any of the network interfaces or dynamically switched
- Loop start, ground start and DPT
- Extends phone lines to remote sites over T1 or Frame Relay (using Voice Compression Module)
- 2-wire interface through an RJ-48 modular connector

#### **Octal FXS Module**

The ADTRAN® ATLAS™ 550 FXS option module provides eight 2-wire interfaces that can operate in the PLAR, Tandem (MEGACOM), or FXS mode and supports PBX circuits, analog phones and modems. The module provides talk battery, off-hook supervision and balanced ringing for short loop or premises applications.

#### **Octal FXO Module**

The ADTRAN FXO module is one of several expansion modules for the ATLAS 550 integrated access device and provides eight foreign exchange office loop interfaces. This module should be selected when a connection to one to eight voice line cards of a key system or PBX is required. PBX extensions may be extended to a remote site by combining a TSU on the remote end with FXS modules. The module can emulate the CO side of a DID (Direct Inward Dial) trunk. The module provides standard 2FXO or DPT functionality to distances of 2400 feet.



**ADTRAN, Inc.**

Attn: Enterprise Networks  
901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963-8000 voice  
256 963-8699 fax  
256 963-8200 fax back

**General Information**  
800 9ADTRAN  
info@adtran.com  
www.adtran.com

**Pre-Sales  
Technical Support**

800 615-1176 toll-free  
application.engineer@adtran.com  
www.adtran.com/support

**Where to Buy**

877 280-8416 toll-free  
channel.sales@adtran.com  
www.adtran.com/where2buy

**Post-Sales  
Technical Support**

888 423-8726  
support@adtran.com  
www.adtran.com/support

**ACES Installation &  
Maintenance Service**

888 874-ACES  
aces@adtran.com  
www.adtran.com/support

**International Inquiries**

256 963 8000 voice  
256 963-6300 fax  
international@adtran.com  
www.adtran.com/international

**For the regional office  
nearest you, visit:**

www.adtran.com/where2buy



ADTRAN is an  
ISO 9001: 2000 certified supplier.



ADTRAN is a  
TL 9000 3.0 certified supplier.

61200310L1-8A May 2002  
Copyright © 2004 ADTRAN, Inc.  
All rights reserved.

# Octal FXS/FXO

## ATLAS 550 Expansion Modules

### Product Specifications

#### Octal FXO Physical Interface

- Modular RJ-45

#### Operating Modes

- FXO (Loop and Ground Start)

#### 2-Wire Impedance

- 600 OHMS +2.16 uF

#### Tip Levels

- -6dB to +6dB – Rx Gain (in 3 dB steps)
- -6dB to +6dB – Tx Gain (in 3 dB steps)

#### Ring Detection

- >20 VAC @ 15-65 Hz
- 0.3 REN per port

#### Other Features

- CLASS Services Supported
- Line Side Answer Supervision
- Distinctive Alerting
- Far End Disconnect

#### Environment

- **Operating:** 0° to 50°C (32° to 122°F)
- **Storage:** -20° to 70°C (-4° to 158°F)
- **Relative Humidity:** Up to 95%, non-condensing

#### Physical

- Modules Dimensions: 7.0" W, 10.0" D, 1.25" H
- **Weight:** 1.5 lbs

#### Agency Approvals

- FCC Part 15 (A), CISPR 22 (A), Industry Canada CS03, UL 1950, CUL IEC 950, FCC Part 68

#### Product Includes

- User Manual

#### Octal FXS Physical Interface

- Modular RJ-45

#### Operating Modes

- FXS (Loop and Ground Start)
- Tandem (E&M Immediate/wink to FXS Conversion)
- Tandem Supervision

#### Ringing

- On Board Ring Generator
- 50 Vrms
- 5 REN per module

#### Loop Range

- 0 to 400 Ohms

#### Other Features

- CLASS Services Supported
- Line Side Answer Supervision
- Loop Reverse Battery
- Far End Disconnect
- Dialtone and Ringback Tone Generators

#### Environment

- **Operating:** 0° to 45°C (32° to 122°F)
- **Relative Humidity:** Up to 95%, non-condensing

#### Agency Approvals

- FCC part 15, Class A, UL, and Canadian UL (CUL)

#### Product Includes

- User Manual

## Ordering Information

Equipment	Part #
Octal FXO Module	1200310L1
Octal FXS Module	1200309L1

Specifications subject to change without notice. ATLAS is a trademark of ADTRAN, Inc. ADTRAN is a registered trademark of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.