

Octal E&M

ATLAS 550 Expansion Module

Product Features

- Eight voice ports operate in 2-wire or 4-wire Type I, II, III, IV, and V signaling modes
- Trunk interfaces to PBX or key system
- Supports transmission only mode for leased line modem applications
- Supports press-to-talk applications using Type V signaling
- Accepts all ATLAS 550 resource modules
- Flash upgradeable

The ADTRAN® ATLAS™ 550 Octal E&M module provides eight ports for 2-wire and 4-wire E&M applications for PBXs, key systems, and leased line analog modems. E&M signaling types I, II, III, IV, and V are supported, as well as a Transmission Only (TO) mode. Type V signaling can be utilized for press-to-talk applications. The module is intended for on-premise applications and therefore makes no provision for sealing current. Signaling originates on the E-lead.

The Octal E&M module can be used in ATLAS 550 applications utilizing dedicated, ISDN, T1, and Frame Relay circuits. Each port provides an RJ-45 interface and can be independently configured. The module installs in any of the four user interface module slots in the ATLAS 550 and is flash upgradeable.





ADTRAN, Inc.

Attn: Enterprise Networks 901 Explorer Boulevard Huntsville, AL 35806

P.O. Box 140000 Huntsville, AL 35814-4000

> 256 963-8000 voice 256 963-8699 fax 256 963-8200 fax back

General Information

800 9ADTRAN info@adtran.com www.adtran.com

Pre-Sales Technical Support

800 615-1176 toll-free application.engineer@adtran.com www.adtran.com/support

Where to Buy

877 280-8416 toll-free channel.sales@adtran.com www.adtran.com/where2buy

Post-Sales Technical Support

888 423-8726 support@adtran.com www.adtran.com/support

ACES Installation & Maintenance Service

888 874-ACES aces@adtran.com www.adtran.com/support

International Inquiries

256 963 8000 voice 256 963-6300 fax international@adtran.com www.adtran.com/international

For the regional office nearest you, visit:

www.adtran.com/where2buy



ADTRAN is an ISO 9000: 2000 certified supplier.



ADTRAN is a TL 9000 3.0 registered company.

61200313L1-8A May 2002 Copyright © 2004 ADTRAN, Inc. All rights reserved.

Octal E&M

ATLAS 550 Expansion Module

Product Specifications

Physical Interface

■ Modular RJ-45

Operating Modes

- 4-Wire E&M
- 2-Wire E&M
- 4-Wire Transmission Only (No signaling)
- 2-Wire Transmission Only (No signaling)

Impedance

- 4W Impedance: 600 Ω
- 2W Impedance: 600 Ω +2.15 uF

Frequency Response

■ 300-3400 hz (+/-1.0dB)

TLP Levels

- TX: -12dB~ +6dB gain, 3dB steps (+12dB~ -6dB TLP)
- RX: 12dB~ +6dB gain, 3dB steps (-12dB~ +6dB TLP)

Signaling Modes

- E-Lead originate
- Types I, II, III, IV, V

Environment

- Operating Temperature: 0° to 50°C, (32° to 122°F)
- Storage Temperature: -20° to 70°C, (-4° to 158°F)
- Relative Humidity: Up to 95%, non-condensing

Physical

- Module Dimensions: 7.0" W, 10.0" D, 1.25" H
- Weight: 1.51 lbs

Agency Approvals

FCC Part 15 (A), CISPR 22 (A), Industry Canada CS03, UL 1950, CUL IEC 950

Product Includes

■ User manual

Ordering Information

Equipment	Part #
Octal E&M Module	1200313L1