



# NT1 ACE3

## Triple NT1

### Product Features

- Three NT1s in a single enclosure
- Optimized for 384 kbps videoconferencing applications
- Supports multiple switch vendors; LUCENT 5ESS™, NT1 DMS-100™, Siemens EWSD, NEC, and National ISDN-1
- LED display to indicate power and network status
- Provides U-interface lightning protection
- Industry-leading five-year North American warranty

**The ADTRAN NT1 ACE3® combines the functionality of the three NT1s in a single device.** Connection to the ISDN network is accomplished via three U-interfaces, and connection to the subscribers' terminal equipment utilizing three S/T-interfaces. The U- and S/T-interfaces on the NT1 ACE3 conform to ANSI and CCITT standards and perform all Layer 1 functions.

The NT1 ACE3 is designed with aesthetics as well as functionality in mind. The unit is enclosed in an attractive, durable plastic housing appropriate for desktop or wall-mount use. The NT1 ACE3 is powered by the external power supply provided with the unit.

The NT1 ACE3 provides 100 ohm bus termination and is protected from lightning and harmful line transients on the network interfaces.

Six LED status indicators on the NT1 ACE3 aid in fault isolation. Indicators display the status for Power, Network Ready, Network and Customer Errors, and Network Test.



#### ADTRAN, Inc.

Attn: Enterprise Networks  
901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963-8000 voice  
256 963-8699 fax  
256 963-8200 fax back

#### General Information

800 9ADTRAN  
info@adtran.com  
www.adtran.com

#### Pre-Sales

#### Technical Support

800 615-1176 toll-free  
application.engineer@adtran.com  
www.adtran.com/support

#### Where to Buy

877 280-8416 toll-free  
channel.sales@adtran.com  
www.adtran.com/where2buy

#### Post-Sales

#### Technical Support

888 423-8726  
support@adtran.com  
www.adtran.com/support

#### ACES Installation & Maintenance Service

888 874-ACES  
aces@adtran.com  
www.adtran.com/support

#### International Inquiries

256 963 8000 voice  
256 963-6300 fax  
international@adtran.com  
www.adtran.com/international

#### For the regional office nearest you, visit:

www.adtran.com/where2buy



ADTRAN is an  
ISO 9000: 2000 certified supplier.



ADTRAN is a  
TL 9000 3.0 certified supplier.

61200236L1-8C July 2002  
Copyright © 2004 ADTRAN, Inc.  
All rights reserved.

# NT1 ACE3

## Triple NT1

## Product Specifications

### NT1 ACE3 Interface

#### Network

- **Line:** 2-wire (TIP and Ring)
- **Operating Mode:** full-duplex
- **Data Rate:** 160 kbps total; 144 kbps available to customer
- **Signal Format:** 2B1Q
- **Output Amplitude:** 2.5 V, zero-to-peak
- **Tx Source Impedance:** as per ANSI T1.601-1992
- **Rx Source Impedance:** as per ANSI T1.601-1992
- **Receiver Sensitivity:** as per ANSI T1.601-1992

#### Customer

- **Line:** 4-wire (Tx and Rx pair)
- **Operating Mode:** full-duplex
- **Data Rate:** 192 kbps total; 144 kbps available to customer
- **Signal Format:** Alternate mark inversion, 100% duty cycle
- **Output Amplitude:** 0.75 V, zero-to-peak
- **Tx Source Impedance:** as per ANSI T1.605-1991
- **Rx Source Impedance:** as per ANSI T1.605-1991
- **Receiver Sensitivity:** as per ANSI T1.605-1991

### Switch Compatibility

- Lucent 5ESS™
- Nortel DMS-100™
- Siemens EWSD
- NEC
- National ISDN-1

### Agency Approvals

- FCC Part 15, Class B
- FCC Part 68
- UL
- CUL
- CSA
- CS03

### Environment

#### Operating Temperature

- 0° to 50°C (32° to 122°F)

#### Storage Temperature

- -20° to 70°C (-4° to 158°F)

#### Relative Humidity

- Up to 95%, non-condensing

### Physical

#### Size

- 1.625" H, 6.375" D, 9.0" W

#### Weight

- 9.5 oz

#### Power

- +12 vDC, 3.3 W dissipation

### Product Includes

- Two 6 ft TRI telephone cables (RJ45 to RJ11)
- 110 V wallmount power supply
- User manual

## Ordering Information

Equipment	Part #
NT1 ACE3	1200236L1



Specifications subject to change without notice. ADTRAN and NT1 ACE3 are registered trademarks of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.