

SFP ONU

2.5G/1.25G GPON Without MAC Functionality

P/N: 1442536F1

Quick Start

DESCRIPTION

The Small Form-Factor Pluggable (SFP) is a single-mode fiber SFP that plugs into an ADTRAN optical interface designed to accept SFPs. The SFP provides a single optical interface to a physical interface, and is intended for use with a Gigabit Passive Optical Network (GPON) module. Medium Access Control (MAC) sublayer functionality, according to IEEE 802 LAN/MAN Standards, is not inside this SFP.

This SFP has a Digital Diagnostic Monitoring (DDM) function with internal calibration.

INSTALLATION

Before installing the equipment, inspect the SFP. If damage has occurred during shipping, file a claim with the carrier, and then contact ADTRAN Customer Support. For more information, refer to the warranty.

To install the SFP into an appropriate module, complete the following steps:

1. Do not remove the protective end cap from the SFP until the fiber optic cable is ready to be connected.
2. Insert the SFP into the SFP cage on the module. Ensure the manufacturer's label on the SFP is facing upward for correct installation.
3. Slide the SFP all the way into the receptacle until there is an audible "click."



CAUTION!

Due to compliance certification requirements, use only SFPs supplied by ADTRAN. ADTRAN cannot certify system integrity with other SFPs.



NOTICE

The latch on the SFP is used to remove the SFP from the cage on the circuit card.

OPERATIONAL SPECIFICATIONS

General

- Module type: SFP
- Fiber/Copper: Fiber
 - ◆ SM/MM: Single Mode Fiber
 - ◆ Single/Dual-fiber: Single-fiber
- Signal Data Rate
 - ◆ Upstream Signaling Speed: 1244 Mb/s
 - ◆ Downstream Signaling Speed: 2488 Mb/s
- Optical Connector: SC
- Applications: GPON ONU
- Distance: 20 km
- Digital Diagnostic Monitoring: SFF8472 Compliant

Optical

- Optical Budget: 26 dB (+/- 1)
- Transmitter
 - ◆ Laser Diode Type: DFB
 - ◆ Tx Central Wavelength: 1310 nm
 - ◆ Tx Output optical power: +0.5 dBm to +5.0 dBm
 - ◆ Tx Spectral width: 1 nm
 - ◆ SMSR: 30 dB
 - ◆ Extinction Ratio: 10 dB
- Receiver
 - ◆ Rx Type: CW Mode Receiver
 - ◆ Rx Central wavelength: 1490 nm
 - ◆ Input optical power: -8.0 dBm to -28.0 dBm
 - ◆ Receiver Overload: -8 dBm
 - ◆ Receiver Sensitivity: -28 dBm

Environmental

Protected Equipment Severe Environment (Outside)

- Operational temperature range: -40°C to +70°C
- Storage temperature range: -40°C to +85°C
- Relative humidity to 5 to 90%, noncondensing

SAFETY AND REGULATORY

ENGLISH



WARNING!

Read all warnings and cautions before installing or servicing this equipment.



CAUTION!

This product is a Class 1 Laser module that complies with FDA 21 CFR 1040.10 and 1040.11 and IEC 60825-1. This product is NRTL Listed and CB Certified to all applicable American and European safety standards. For continued compliance with the above standards, install only ADTRAN-approved Class 1 Laser Modules in ADTRAN products. For a list of ADTRAN-approved SFPs and XFPs, see <http://www.adtran.com/SFP>. ADTRAN cannot certify system integrity with other laser modules.



CAUTION!

- Electrostatic Discharge (ESD) can damage electronic modules. When handling modules, wear an antistatic discharge wrist strap to prevent damage to electronic components. Place modules in antistatic packing material when transporting or storing. When working on modules, always place them on an approved antistatic mat that is electrically grounded.
- The SFP meets or exceeds all the applicable requirements of NEBS, Telcordia GR-63-CORE, and GR-1089-CORE. The product is intended for deployment in locations where the NEC applies (for example, Customer Premises).
- Per GR-1089-CORE the ADTRAN system that the SFP is being deployed in is designed and intended for installation as part of a Common Bonding Network (CBN). The ADTRAN system that the SFP is being deployed in is not designed nor intended for installation as part of an Isolated Bonding Network (IBN).
- This product can be installed in a DC-I (isolated) or DC-C (common) configuration.
- The chassis frame ground terminal of the product this SFP is installed in (if it has a frame ground) must be connected to an earth ground to ensure that the exposed metal (i.e., front panels, SFP/XFP modules) on the product is properly grounded by way of the backplane connector.



NOTE

- The Gigabit Ethernet port(s) are optical and therefore are not classified as any type of port as defined in Appendix B of GR-1089-CORE.
- This product is designed to be deployed in GR-3108-CORE environmental class 1, class 2, and class 3 as defined in GR-3108-CORE.
- This product is NRTL Listed to the applicable UL Standards. The product is designed to meet the applicable requirements of Telcordia for GR-3108-CORE and GR-1089-CORE.
- This product has also been evaluated to international safety standards EN 60950-1, AS/NZS 60950.1, and IEC 60950-1. This product meets the requirements for CE marking under the EMC Directive and Low Voltage Directive. Standards used to demonstrate Compliance are EN 300 386 and EN 60950-1.
- This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions:
 1. This device may not cause harmful interference.
 2. This device must accept any interference received, including interference that may cause undesired operation.
- Changes or modifications not expressly approved by ADTRAN could void the user's authority to operate this equipment.
- This product is designed to meet the following environmental classes:
 - ◆ ETSI EN 300 019-2-1 "Classification of environmental conditions; Storage Class" 1.2
 - ◆ ETSI EN 300 019-2-2 "Classification of environmental conditions, Transportation", Class 2.3
 - ◆ ETSI EN 300 019-2-3 "Classification of environmental conditions, Stationary use at weather protected locations", Class 3.1E
- This product is designed to function without degradation during exposure to all test severities per Class 3.3 of ETSI EN 300 019-1-3.
- This product meets EU RoHS Directive. Refer to www.adtran.com for further information on RoHS/WEEE.

FRANÇAIS

AVERTISSEMENT!

Lisez tous les avertissements et mises en garde avant l'installation de cet équipement ou la réalisation de toute opération de maintenance.

ATTENTION!

Ce produit est un module laser de classe 1 qui est conforme à la FDA 21 CFR 1040.10 et 1040.11 et IEC 60825-1. Ce produit est NRTL et Certifié CB à toutes les normes de sécurité applicables américains et européens. Pour maintenir la conformité avec les normes ci-dessus, installer des modules laser de classe 1 ne ADTRAN approuvés dans les produits d'ADTRAN. Pour une liste des SFP et XFP ADTRAN approuvés, voir <http://www.adtran.com/SFP>. ADTRAN ne peut certifier l'intégrité du système avec d'autres modules laser.

ATTENTION!

- L'ESD (décharge électrostatique) peut endommager les modules électroniques. Lors de la manipulation des modules, portez un bracelet de décharge antistatique pour éviter d'endommager les composants électroniques. Placez les modules dans un emballage antistatique lors du transport ou du stockage. Lorsque vous travaillez sur les modules, placez-les toujours sur un tapis antistatique certifié muni d'un branchement de mise à la terre.
- La borne de terre de châssis doit être connecté à une prise de terre pour assurer que le métal exposé (tels que les panneaux avant, des modules SFP / XFP) sur le produit est correctement mis à la terre via le connecteur de fond de panier.

REMARQUE

Ce produit est conforme à la directive européenne RoHS. Reportez-vous à www.adtran.com pour de plus amples renseignements sur RoHS.

DEUTSCH

WARNUNG!

Lesen Sie sich alle Warn- und Sicherheitshinweise durch, bevor Sie dieses Gerät installieren oder warten.

VORSICHT!

Dieses Produkt ist ein Klasse 1 Laser -Modul, das mit der FDA 21 CFR 1040.10 und 1040.11 und IEC 60825-1 entspricht. Dieses Produkt wurde NRTL gelistet und CB Certified allen geltenden amerikanischen und europäischen Sicherheitsstandards. Für die ständige Einhaltung der oben genannten Normen, installieren Sie nur ADTRAN zugelassene Klasse 1 Lasermodule in ADTRAN Produkte. Eine Liste der ADTRAN zugelassene SFPs und XFPs finden Sie unter <http://www.adtran.com/SFP>. ADTRAN kann nicht die Unversehrtheit des Netzes mit anderen Laser-Module zertifizieren.

VORSICHT!

- Elektrostatische Entladung (ESD) können elektronische Baugruppen beschädigt werden. Beim Umgang mit Modulen , tragen Sie eine Antistatikarmband, um Schäden an elektronischen Bauteilen zu verhindern. Ort -Module in antistatische Verpackung, beim Transport oder Lagerung. Bei Arbeiten an Modulen immer legen Sie sie auf einer zugelassenen antistatische Unterlage, die elektrisch geerdet ist.
- Der Fahrgestellrahmen Erdanschluß muß zu einer Erde verbunden werden, um sicherzustellen, dass das freiliegende Metall (dh Frontplatten, SFP / XFP-Module) auf dem Produkt richtig über den Backplane-Anschluss geerdet ist.

HINWEIS

Dieses Produkt erfüllt die EU RoHS Richtlinie. Bitte besuchen Sie www.adtran.com für ausführlichere Informationen zu RoHS/ WEEE.

Documentation for ADTRAN Network Solutions products is available for viewing and download directly from the ADTRAN Support Community website.

Go to: <https://supportforums.adtran.com/welcome>

Registration is required.

ADTRAN offers training courses on our products, including customized training and courses taught at our facilities or at customer sites.

For inquiries, go to: <http://adtran.com/training>

The following online documents and resources provide additional information for this product:

ADTRAN Pluggable Optics Compatibility Matrix (online tool, go to: <http://www.adtran.com/pluggableoptics>)

Warranty: ADTRAN will replace or repair this product within the warranty period if it does not meet its published specifications or fails while in service. Warranty information can be found online at www.adtran.com/warranty.

Trademarks: Brand names and product names included in this document are trademarks, registered trademarks, or trade names of their respective holders.

©2018 ADTRAN, Inc. All Rights Reserved.



ADTRAN CUSTOMER CARE:
From within the U.S. 1.888.423.8726
From outside the U.S. +1 256.963.8716
PRICING AND AVAILABILITY 1.800.827.0807

