Updated: 6/16/2008

# ISU 128

## 128 Kbps ISDN Service Unit

#### **Front View**



#### **Rear View**



Updated: 6/16/2008

#### **Physical Interfaces**

- **Integrated Ports** 
  - One RJ-45 for ISDN BRI U Network Interface
  - One V.35 DTE Interface
  - One EIA-530/EIA-232 DTE Interface
  - One EIA-366 DTE Dial Interface

#### **Performance and Design Considerations**

■ Network Interface

Physical Interface: RJ-45

ISDN Switch Types

■ National ISDN-1

■ Lucent 5ESS

■ Nortel DMS-100

NEC

Dialing Selections

Manual or Automatic Stored Number Dialing

■ DTR Assertion

■ In-Band DTE Dialing: V.25 bis, AT Commands

■ Dial Interface: EIA-366

■ DTE Interface Data Rates

■ 2400 bps to 128 kbps synchronous

■ 300 bps to 115.2 kbps asynchronous

#### **Physical Specifications**

■ Chassis: Stand Alone

■ Dimensions: 2.25" H, 7.5" W, 10" D

■ Weight: 3 lbs

Operating Temperature: 32°F to 122°F (0°C to 50°C)
Mean Time Between Failure (MTBF): 639,080 Hrs

#### **Power Specifications**

■ AC Power: 115 VAC

■ Power Consumption: 8 W, 258 BTU

#### **Agency Approvals**

■ FCC part 15 Class B, FCC Part 68

■ UL, CUL

#### Warranty

■ 5 Year (Repair & Return)

■ www.ADTRAN.com/Warranty

#### **Product Includes**

■ All ISU units ship with the following:

• One 7 ft. telephone cable

User Manual

For additional product information including data sheets, manuals, installation guides, etc. please visit: <a href="https://www.ADTRAN.com/ISU">www.ADTRAN.com/ISU</a>

For network design assistance or general inquires please visit: <u>www.ADTRAN.com/DesignAssistance</u>

### Ordering Information

ISU 128	Part Number
ISU 128	1202029L2

Updated: 6/16/2008

#### **DISCLAIMER**

ADTRAN provides the foregoing application description solely for the reader's consideration and study, and without any representation or suggestion that the foregoing application is or may be free from claims of third parties for infringement of intellectual property rights, including but not limited to, direct and contributory infringement as well as for active inducement to infringe. In addition, the reader's attention is drawn to the following disclaimer with regard to the reader's use of the foregoing material in products and/or systems. That is:

ADTRAN SPECIFICALLY DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ADTRAN BE LIABLE FOR ANY LOSS OR DAMAGE, AND FOR PERSONAL INJURY, INCLUDING BUT NOT LIMITED TO, COMPENSATORY, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR OTHER DAMAGES