ISU 512e

512 Kbps ISDN Inverse Multiplexer with SNMP

Front View



Rear View



Physical Interfaces

Integrated Ports

- Four RJ-45s for ISDN BRI U Network Interfaces
- One V.35 DTE Interface
- One EIA-366 DTE Dial Interface
- One 10 Base-T Ethernet Interface (SNMP Only)

Performance and Design Considerations

- Network Interface
 - Physical Interface: RJ-45
 - ISDN Switch Types
 - National ISDN-1
 - Lucent 5ESS
 - Nortel DMS-100
 - NEC
 - Dialing Selections
 - Manual or Automatic Stored Number Dialing
 - DTR Assertion
 - In-Band DTE Dialing: V.25 bis, AT Commands
 - Dial Interface: EIA-366
- DTE Interface Data Rates
 - 56 bps to 512 kbps synchronous

Physical Specifications

- Chassis: Stand Alone
- Dimensions: 2.5" H, 7.875" W, 10.5" D
- Weight: 3 lbs
- Operating Temperature: 32°F to 122°F (0°C to 50°C)
- Mean Time Between Failure (MTBF): 436,238 Hrs

Power Specifications

- AC Power: 115 VAC
- Power Consumption: 8 W, 258 BTU

Warranty

- 5 Year (Repair & Return)
- <u>www.ADTRAN.com/Warranty</u>

Product Includes

- All ISU 512 units ship with the following:
 - Four 7 ft. telephone cable
 - User Manual

For additional product information including data sheets, manuals, installation guides, etc. please visit: <u>www.ADTRAN.com/ISU</u>

For network design assistance or general inquires please visit: <u>www.ADTRAN.com/DesignAssistance</u>

Ordering Information

| TSU 100/100e | Part Number |
|--------------|-------------|
| ISU 512e | 1203086L1 |

DISCLAIMER

ADTRAN provides the foregoing application description solely for the reader's consideration and study, and without any representation or suggestion that the foregoing application is or may be free from claims of third parties for infringement of intellectual property rights, including but not limited to, direct and contributory infringement as well as for active inducement to infringe. In addition, the reader's attention is drawn to the following disclaimer with regard to the reader's use of the foregoing material in products and/or systems. That is:

ADTRAN SPECIFICALLY DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ADTRAN BE LIABLE FOR ANY LOSS OR DAMAGE, AND FOR PERSONAL INJURY, INCLUDING BUT NOT LIMITED TO, COMPENSATORY, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR OTHER DAMAGES