Updated: 6/13/2008

ISU 512

512 Kbps ISDN Inverse Multiplexer

Front View



Rear View



Updated: 6/13/2008

Physical Interfaces

- Integrated Ports
 - Four RJ-45s for ISDN BRI U Network Interfaces
 - One V.35 DTE Interface
 - One EIA-530 DTE Interface
 - One EIA-366 DTE Dial Interface

Performance and Design Considerations

■ Network Interface

Physical Interface: RJ-45

ISDN Switch Types

■ National ISDN-1

■ Lucent 5ESS

■ Nortel DMS-100

NEC

Dialing Selections

Manual or Automatic Stored Number Dialing

■ DTR Assertion

■ In-Band DTE Dialing: V.25 bis, AT Commands

Dial Interface: EIA-366DTE Interface Data Rates

■ 56 bps to 512 kbps synchronous

Physical Specifications

■ Chassis: Stand Alone

■ Dimensions: 2.5" H, 7.875" W, 10.5" D

■ Weight: 3 lbs

Operating Temperature: 32°F to 122°F (0°C to 50°C)
Mean Time Between Failure (MTBF): 639,080 Hrs

Power Specifications

■ AC Power: 115 VAC

■ Power Consumption: 8 W, 258 BTU

Warranty

■ 5 Year (Repair & Return)

■ www.ADTRAN.com/Warranty

Product Includes

■ All ISU 512 units ship with the following:

• One 7 ft. telephone cable

User Manual

For additional product information including data sheets, manuals, installation guides, etc. please visit: www.ADTRAN.com/ISU

For network design assistance or general inquires please visit: <u>www.ADTRAN.com/DesignAssistance</u>

Ordering Information

| TSU 100/100e | Part Number |
|----------------------|-------------|
| ISU 512 | 1202086L1 |
| RS-530 to V.35 Cable | 1200072L1 |
| RS-366 Y Cable | 1200120L1 |

Updated: 6/13/2008

DISCLAIMER

ADTRAN provides the foregoing application description solely for the reader's consideration and study, and without any representation or suggestion that the foregoing application is or may be free from claims of third parties for infringement of intellectual property rights, including but not limited to, direct and contributory infringement as well as for active inducement to infringe. In addition, the reader's attention is drawn to the following disclaimer with regard to the reader's use of the foregoing material in products and/or systems. That is:

ADTRAN SPECIFICALLY DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ADTRAN BE LIABLE FOR ANY LOSS OR DAMAGE, AND FOR PERSONAL INJURY, INCLUDING BUT NOT LIMITED TO, COMPENSATORY, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR OTHER DAMAGES