Updated: 4/22/2009



Front View



Rear View



Updated: 4/22/2009

Physical Interfaces

- Integrated Ports
 - One T1/FT1 Network Interface (Integrated CSU/DSU)
 - One V.35 Nx56/64 DTE Interface
 - Bantam Test Jacks
 - Chain In/Out Ports

Physical Specifications

■ Chassis: Stand Alone

■ Dimensions: 1.5" H, 9.0" W, 6.25" D

■ Weight: 2 lbs

Operating Temperature: 32°F to 122°F (0°C to 50°C)
Mean Time Between Failure (MTBF): 903,580 Hrs

Performance and Design Considerations

■ Network Interface

Physical Interface: RJ-48cFraming: D4 (SF)/ESFLine Code: AMI/B8ZS

T1 Timing: Network, Internal, or DTEDS0 Assignment: Contiguous or Alternating

V.35 DTE Interface

Physical Interface: V.35 (Winchester Type 34 Pin)

■ BIT Rate: 56 Kbps to 1.536 Mbps

V.35 Cable not included

Performance Monitoring

- Performance Data
 - BPVs/CRCs, ES, SES, UAS, %AS, %EF SEC
 - Alarms and Error Rates
- Reports
 - NI information stored for 24 Hrs in15 minute intervals
- PRMS
 - ANSI Performance Report
 - Messages (User Selectable)

Power Specifications

■ AC Power: 115 VAC

■ Power Consumption: 5 W, 17 BTU

■ Max Current Draw: 0.15A

Agency Approvals

- FCC part 15 Class A, FCC Part 68
- CUL

Warranty

- 5 Year (Repair & Return)
- www.ADTRAN.com/Warranty

Product Includes

- All TSU LT units ship with the following:
 - One 15 ft. T1 Cable
 - Power Cord 6 ft.
 - Loop Back Plug
 - Documentation CD

Ordering Information

TSU LT	Part Number
TSU LT	1203060L1

DISCLAIMER

ADTRAN provides the foregoing application description solely for the reader's consideration and study, and without any representation or suggestion that the foregoing application is or may be free from claims of third parties for infringement of intellectual property rights, including but not limited to, direct and contributory infringement as well as for active inducement to infringe. In addition, the reader's attention is drawn to the following disclaimer with regard to the reader's use of the foregoing material in products and/or systems. That is:

ADTRAN SPECIFICALLY DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ADTRAN BE LIABLE FOR ANY LOSS OR DAMAGE, AND FOR PERSONAL INJURY, INCLUDING BUT NOT LIMITED TO, COMPENSATORY, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR OTHER DAMAGES